



For material recycling information please refer to the Allseating End of Life Recovery and List of Recycling Facilities, which is available at www.allseating.com



Tools: #2 #3 Phillips Head, Rubber Mallet or Hammer, Allen Key

Skill Set: Good manual dexterity.

Estimated Time: 15min per chair.

Steps:

1. Back Rest - 2min

Turn the chair upside down so the bottom is visible. Locate 1 fastener located underside of the frame and unfasten. Pull backrest upward to remove from chair frame.

Incase of double or triplet lounge chair repeat step 1 again.

2. Seat - 2min

Turn the chair upside down so the bottom is visible. Locate 1 fastener located underside of the frame and unfasten. Pull seat upward to remove seat from chair frame.

Incase of double or triplet lounge chair repeat step 2 again.

3. Side Panel/Lounge Closed Armpad - 4min

Turn the chair upside down, so the bottom is visible. Locate two fasteners locate underside of the frame and unfasten. Remove the side panel from arm by pulling downward. Flip the chair to the opposing side and repeat the process.

4. Arm Pad - 2min

Apply force to pull the arm pad upward to remove from the arm or carefully insert the tip of screwdriver in between the arm pad and arm. Push forward the handle of screwdriver until both pry apart.

5. Feet Glides - 2min

Once both the seat and back are removed from the frame, turn the chair upside down to access glides. With pliers, firmly grasp the glide and wiggle upward until free. Repeat process for all four feet.

6. Arm - 3min

Turn the chair upside down so the bottom is visible. Locate the four fasteners located on the underside of frame and unfasten. Remove the arm from chair frame. Flip the chair to the opposing side and repeat the process.